KOHLER, Faucets

Geometric Insight[™]

DM Faucet w/ Mixer K-13468

Features

- 0.5 gal/min (1.9 l/min) flow rate.
- Factory set 30 second max. continual run cycle.
- Vandal resistant aeroator.
- 24" (610 mm) flexible supply hoses for easy installation.
- 5-5/16" (135 mm) spout reach.
- Less drain.

Material

Brass construction.

Technology

- Requires an AC power supply.
- Electronic Insight[™] Sensor Technology for accurate and consistent activation.

Installation

- Single-hole mounting.
- Above-counter valve for easy installation and maintenance.

Required Accessories

K-13480 AC Single Supply

or

K-13481 Multi-outlet Power Supply

Optional Accessories

1101643 Large Concealed Spray 0.5 gpm (1.9 l/min)

1139288 Large Concealed Spray Aerated 1.0 gpm (3.8 l/min)

1139289 Large Concealed Laminar 1.0 gpm (3.8 l/min)

1139290 Large Concealed Aerated 1.5 gpm (5.7 l/min)

1100596 Large Concealed Laminar 1.5 gpm (5.7 l/min)



ADA	CSA B651	ОВС

Codes/Standards

ASME A112.18.1/CSA B125.1

NSF 372

All applicable US Federal and State material

regulations

DOE - Energy Policy Act 1992

ADA

ICC/ANSI A117.1

CSA B651

OBC

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.


Color	Code	Description
	СР	Polished Chrome
	VS	Vibrant® Stainless





Geometric Insight[™]

DM Faucet w/ Mixer K-13468



Technical Information

All product dimensions are nominal.

Valve body: Machined Brass

Spout:

Spout reach: 5-5/16" (135 mm)

Faucet:

Flow rate: 0.5 gal/min (1.9 l/min)

Notes

Install this product according to the installation guide.

A 1-1/4" (32 mm) minimum to 1-1/2" (38 mm) maximum diameter mounting hole is required.

The minimum distance between the back of the faucet spout and the wall must be 1-3/4" (44 mm). This will allow proper clearance for setscrew access.

The maximum distance between the bathroom sink basin edge to the base of the faucet spout must be 1-3/4" (44 mm).

The maximum height of the lip basin should be 3/4" (19 mm).

Product includes rosebud spray aerator. Other aerator styles are available.

This product requires an AC power supply (not included).

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

